

FULL ROUND GUY MARKER WITH SPIRAL PIGTAIL

INSTALLATION INSTRUCTIONS





STEP 1

Position Guy Marker so that top of Marker is upward on the strand.

Note: the TOP end is located opposite of the end with the zip tie.



STEP 2

Place the strand through the slotted "V" opening and push Marker down onto the strand until you get to the beginning of the pigtail.



STEP 3

Pull the pigtail out of the Guy Marker.



STEP 4

Before wrapping the pigtail, make sure that the bottom end of Marker is at the desired location. Pull Marker out slightly away from the strand and wrap pigtail onto the strand.



STEP 5

With pigtail completely wrapped onto strand, continue to place the strand through the slotted “V” opening and push Marker down onto the strand until it is completely installed.



STEP 6

Insert zip tie strap through the two slots.



STEP 7

Wrap the zip tie strap around the Marker and place the zip tie strap through its self-locking tab.



STEP 8

Complete the Guy Marker installation by pulling the zip tie strap to tighten securely.

Note: The Marker may be slid downward to desired location but will resist upward movement.

About Hubbell Power Systems:

TD_06_033_E

Hubbell Power Systems (HPS) manufactures a wide variety of transmission, distribution, substation, OEM, underground and communications products used by utilities. HPS products are also used in the civil construction, transportation, gas and water industries. Our product line includes construction, switching and protection products, hot line tools, insulators, arresters, pole line hardware, cable accessories, test equipment, transformer bushings, connectors, grounding equipment and polymer precast enclosures and equipment pads.

Hubbell has a policy of continuous product improvement. Please visit hubbellpowersystems.com to confirm current design specifications.

HUBBELL[®]
Power Systems, Inc.

©Copyright 2014 Hubbell Incorporated | www.hubbellpowersystems.com | Adjust-A-Grip Installation

